



SUNPARK
ELECTRONICS CORP.

16200 S. Figueroa St., Gardena Ca 90248
Tel: 310-324-8880 Fax: 310-324-4020
e-mail: info@sunpkco.com

LED Vanity Specification

FL2103D-B / FL2105D-B / FL2106D-B



- * Housing: Die-formed cold rolled steel
- * Shade: High Performance Acrylic for LED application
- * LED Driver: 120V ~ 277V, constant current type
- * Certification: ETL / cETL, Energy Star
- * Finish: -62 Satin Nickel. -30 Oil Rubbed Bronze -06 White
- * LED: Nichia or LG, 50,000 hours rating
- * Color Temperature Option: 3000K or 3500K or 4000K or 5000K
- * LED CRI: 80 min
- * Warranty: 5 years on LED and LED driver

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (Typ)	Dimensions (L x W x H)	Finish	Energy Star
FL2103D-B-3000K	120V ~ 277V	24W	3000K / 80	1785	24.5" x 5.5" x 4.0"	Silver / Plastic	Yes
FL2103D-B-4000K	120V ~ 277V	24W	4000K / 80	1850	24.5" x 5.5" x 4.0"	Silver / Plastic	Yes
FL2105D-B-3000K	120V ~ 277V	37W	3000K / 80	2910	36.5" x 5.5" x 4.0"	Silver / Plastic	Yes
FL2105D-B-4000K	120V ~ 277V	37W	4000K / 80	3000	36.5" x 5.5" x 4.0"	Silver / Plastic	Yes
FL2106D-B-3000K	120V ~ 277V	49W	3000K / 80	3420	48.5" x 5.5" x 4.0"	Silver / Plastic	Yes
FL2106D-B-4000K	120V ~ 277V	49W	4000K / 80	3520	48.5" x 5.5" x 4.0"	Silver / Plastic	Yes