

LED Lighting Fixture Specification

FL5524D / FL5539D / FL5554D



- * **Application:** Vanity
- * **Housing:** Die-formed cold-rolled steel
- * **Shade:** High transmission acrylic creates excellent light distribution and uniformity
- * **LED:** High efficiency, high CRI, binned and mixed to reach uniform light and color
- * **5 years warranty on driver and LED module**
- * **Certification:** ETL , Energy Star

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (typ)	Size (L x W x H)	Finish
FL5524D-3000K	120V	19W	3000K / 80	1420	25.5" x 4.8" x 4.5"	Satin Nickel
FL5524D-4000K	120V	19W	4000K / 80	1500	25.5" x 4.8" x 4.5"	Satin Nickel
FL5539D-3000K	120V ~ 277V	23W	3000K / 80	1800	35.5" x 4.8" x 4.5"	Satin Nickel
FL5539D-4000K	120V ~ 277V	23W	4000K / 80	1900	35.5" x 4.8" x 4.5"	Satin Nickel
FL5554D-3000K	120V ~ 277V	38W	3000K / 80	3000	46.5" x 4.8" x 4.5"	Satin Nickel
FL5554D-4000K	120V ~ 277V	38W	4000K / 80	3160	46.5" x 4.8" x 4.5"	Satin Nickel

- * **Color Temperature Option:** 3500K & 5000K
- * **Finish Option:** Oil Rubbed Bronze



16200 S. Figueroa St. Gardena Ca 90248
Tel: 310-324-8880 Fax: 310-324-4020
[e-mail: info@sunpkco.com](mailto:info@sunpkco.com)